

Dimensions mm[inch]
 tolerances acc. to DIN ISO 2768-m
 Toleranzen gem. DIN ISO 2768-m

Isometric
 Scale 1:2
 Maßstab 1:2

Housing

Cable
 flat cable LIYZ 2x0,14qmm
 Flachkabel LIYZ 2x0,14qmm

Terminals/Connector
 Ends tinned
 Enden verzinkt

Schematic

Marking
 according to EN60062/factory code
 gem. EN60062/Fertigungsstätte

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In	Measured at room temp. 20 ° C overdrive 40%	43		64	
Test equipment			MS-		

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - No.					
Contact - form					
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			3	W
Switching voltage	DC or Peak AC			175	V
Carry current	DC or Peak AC			1,2	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			1.017	mOhm
Housing material					
Case color					
Sealing compound			Polyurethan		

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		70	°C
Operating temperature	cable moved	-5		70	°C
Storage temperature		-30		70	°C
Safety class	DIN EN 60529				

Cable specification	Conditions	Min	Typ	Max	Unit
Cable type					
Cable material					
Cross section					

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a resistor is recommended.			
Mounting advice		Magnetically conductive screws must not be used.			
Mounting advice		Decreased switching distances by mounting on iron.			
Tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm