



LAYOUT
 pitch 2.54 mm/Top view


MARKING



Pins: Ø0.65 mm
 L = 3.2 ± 0.3 mm
 Material: Cu-alloy tinned

Coil polarity must be observed!
 In the operating of latching relays, the contact is closed by the application of a positive pulse (>=2ms) to one of the two coils, via the pin marked "+". This condition is maintained until one of the "+" pins receives a negative pulse (>=2ms).

MEDER-Label
 Type/Layout
 Production code,
 EN60062/Factory code

 dimensions / Abmessungen (mm)
 unspecified tolerances acc. to DIN ISO 2768-m

Coil Data at 20 °C	Conditions	Min	Typ	Max	Unit
Coil resistance S1		4.560	5.060	5.560	Ohm
Coil resistance S2		4.560	5.060	5.560	Ohm
Coil voltage			12	18	VDC
Rated power			29		mW
Thermal Resistance			56		K/W
Pull-In voltage		0,8		8,4	VDC
Drop-Out voltage		0,8		8,4	VDC

Contact data 66	Conditions	Min	Typ	Max	Unit
Contact-No.				66	
Contact-form				E - bistable NO	
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage (>20 AT)	DC or Peak AC			200	V
Switching current	DC or Peak AC			0,5	A
Carry current	DC or Peak AC			1,25	A
Contact resistance static	measured with nominal voltage at 20 °C			150	mOhm
Insulation resistance	RH <45 %, 100 VDC test voltage	10			GOhm
Breakdown voltage (>20 AT)	according to IEC 255-5	225			VDC
Release time	measured with no coil excitation			0,1	ms
Operate time incl. bounce	measured with nominal voltage at 20 °C			0,5	ms
Capacitance	@ 10 kHz across open switch		0,2		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Insulation resistance Coil/Contact	RH <45%, 200 VDC test voltage	1.000			GOhm
Insulation voltage Coil/Contact	according to IEC 255-5	2			kV AC
Housing material				Metal/magnetic shield/Fe	
Sealing compound				Polyurethan	
Connection pins				Copper alloy tin plated	
number of contacts				1	



Products for tomorrow...

Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
8812171700
Item:
BE12-1E66-M
BE12-1E71-M

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Ambient temperature		-20		70	°C
Storage temperature		-40		105	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C
Cleaning		fully sealed			

Modifications in the sense of technical progress are reserved

Designed at: 02.02.09 Designed by: WKOVACS Approval at: 06.02.09 Approval by: KOLBRICH
Last Change at: 06.02.09 Last Change by: ALICHTENSTEIN Approval at: 06.02.09 Approval by: KOLBRICH

Version: 03