



*Products for tomorrow...*

Headquarter Europe  
 MEDER electronic AG  
 Friedrich-List Strasse 6  
 D-78234 Engen-Welschingen  
 Tel.: +49(0)7733-9487-0  
 Fax: +49(0)7733-9487-32  
 eMail: [info@meder.com](mailto:info@meder.com)  
 Internet: [www.meder.com](http://www.meder.com)

Headquarter USA  
 MEDER electronic Inc.  
 766 Falmouth Rd  
 Mashpee, MA 02649  
 Phone: +1/ 508-539-0002  
 Fax: +1/ 508-539-4088  
 eMail: [salesusa@meder.com](mailto:salesusa@meder.com)



**Reed Relay:** BE12-1A74-M

**Part Number:** 8812174200


**Dimensions (mm)**

**Layout / Pitch** 2,54 mm / Top View

**Marking**



MEDER-Label  
 Type  
 Layout  
 Production-  
 Code-  
 EN60062  
 /Factory Code



Pins:  $\varnothing$  0,65 mm / L 3,2 ± 0,3 mm

Coil/Relay Characteristics	Conditions at 20°C	Min.	Typ.	Max.	Units
Coil Resistance		1931	2145	2360	$\Omega$
Nominal Voltage			12		VDC
Nominal Rated Power			67		mW
Thermal Resistance			69		K / W
Operate Voltage				8,4	VDC
Release Voltage		1,0			VDC

Contact Data 74 (Form A/Dry)					
Contact Rating	Any combination of the switching voltage and current must not exceed the given rated power			30	W
Switching Voltage	DC / AC			200 /250	V
Switching Current	DC or Peak AC			1,0	A
Carry Current	DC or Peak AC			2,5	A
Static Contact Resistance (initial)	Measured with Nominal Voltage			120	m $\Omega$
Insulation Resistance	RH 45%	10 <sup>11</sup>			$\Omega$
Breakdown Voltage		430			VDC
Operate Time, including Bounce	Measured with Nominal Voltage			0,5	ms
Release Time	Measured with no coil suppression			0,2	ms
Capacitance			0,2		pF

Environmental Data					
Insulation Resistance Coil to Contact	RH 45%	10 <sup>12</sup>			$\Omega$
Dielectric Strength Coil to Contact		2,0			kV AC
Shock	½ sine wave, duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating Temperature	10°C/min max. allowable	-20		70	°C
Storage Temperature	10°C/min max. allowable	-40		105	°C
Soldering Temperature	5 sec. at			260	°C
Cleaning				fully sealed	
Material of Case				Metal / Magnetic Shielding / Fe	
Sealing Compound				Polyurethan	
Material of Pins				Cu-alloy tinned	
Remarks					

Customer / Customer part number	Standard Part
---------------------------------	---------------