



| Special Product Data | Conditions | Min | Typ | Max | Unit |
|----------------------|---|-------------|-----|-----|------|
| Contact - form | | A - NO | | | |
| Contact rating | Any DC combination of V & A not to exceed their individual max.'s | | | 10 | W |
| Switching voltage | DC or Peak AC | | | 200 | V |
| Switching current | DC or Peak AC | | | 0,5 | A |
| Carry current | DC or Peak AC | | | 1 | A |
| Sensor-resistance | measured with 40% overdrive Sensor deactivated | | | 300 | mOhm |
| Housing material LS | | PP | | | |
| Case colour | | white | | | |
| Material of float | | PP | | | |
| Sealing compound | | Polyurethan | | | |

| Environmental data | Conditions | Min | Typ | Max | Unit |
|-----------------------|-----------------|-----|-----|-----|------|
| Operating temperature | cable not moved | -30 | | 80 | °C |
| Operating temperature | cable moved | -5 | | 80 | °C |
| Storage temperature | | -30 | | 80 | °C |

| Cable specification | Conditions | Min | Typ | Max | Unit |
|---------------------|------------|-------------|-----|-----|------|
| Cable type | | round cable | | | |
| Cable material | | PVC | | | |
| Cross section | | 0,14 mm² | | | |

| General data | Conditions | Min | Typ | Max | Unit |
|-------------------|------------|---|-----|-----|------|
| Mounting advice | | over 5m cable, a resistor is recommended. | | | |
| Tightening torque | | | | 0,5 | Nm |