



| Contact data 66 | Conditions | Min | Typ | Max | Unit |
|----------------------------|---|-----|-----|------|------|
| Contact-form | | | A | | |
| Contact rating | Any DC combination of V & A not to exceed their individual max.'s | | | 10 | W |
| Switching voltage (<21 AT) | DC or Peak AC | | | 180 | V |
| Switching current | DC or Peak AC | | | 0,5 | A |
| Carry current | DC or Peak AC | | | 1,25 | A |

| Special Product Data | Conditions | Min | Typ | Max | Unit |
|-------------------------|------------|-----|-----------------|-------|------|
| Contact - form | | | A - NO | | |
| Sensor-resistance | | | | 1.500 | mOhm |
| Housing material LS | | | stainless steel | | |
| Material of float | | | stainless steel | | |
| Sealing compound | | | Polyurethan | | |
| Reach / RoHS conformity | | | yes | | |

| Environmental data | Conditions | Min | Typ | Max | Unit |
|-----------------------|-------------------|-----|-----|-----|------|
| Shock | | | | 50 | g |
| Vibration | from 10 - 1200 Hz | | | 20 | g |
| Operating temperature | | -30 | | 70 | °C |
| Operating temperature | | -5 | | 70 | °C |
| Storage temperature | | -30 | | 70 | °C |

| Cable specification | Conditions | Min | Typ | Max | Unit |
|---------------------|------------|-----|-------------|-----|------|
| Cable type | | | round cable | | |
| Cable material | | | PVC | | |
| Cross section | | | 0.14 sq-mm | | |

| General data | Conditions | Min | Typ | Max | Unit |
|-------------------|------------|---|-----|-----|------|
| Mounting advice | | over 5m cable, a resistor is recommended. | | | |
| Tightening torque | | | | 5 | Nm |